



## ARIAL 4T MOTORCYCLE SAE 10W-40



This oil is special developed for the lubrication of four-stroke motorcycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the most important motorcycle producers and has its performance demonstrated in the field.

---

**SKU:** 502010

**Categories:** [4-тактови моторни масла](#)

## PRODUCT DESCRIPTION

A new generation semi-synthetic engine oil for four-stroke motorcycles formulated with high quality mineral and synthetic base oils combined with special developed balanced additives to achieve the following properties:

- a high and stable viscosity index
- good cold start properties
- optimal friction characteristics
- a very strong protection against wear, corrosion and foaming
- a very good detergency and dispersion

### Application:

This oil is special developed for the lubrication of four-stroke motorcycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the most important motorcycle producers and has its performance demonstrated in the field.

### Performance Level:

API SL  
JASO MA2  
JASO MA

**Typicals:**

Density at 15 °C, kg/l: 0,871

Viscosity -25 °C, mPa.s: 4050

Viscosity 40 °C, mm<sup>2</sup>/s: 87,00Viscosity 100 °C, mm<sup>2</sup>/s: 13,80

Viscosity Index: 163

Flash Point COC, °C: 210

Pour Point, °C: -30

Total Base Number, mgKOH/g: 7,7

Sulphate Ash, %: 0,94

**Packaging:**

| litres | packing     | per box | per pallet |
|--------|-------------|---------|------------|
| 1      | canister    | 12      | *600       |
| 5      | canister    | 4       | *120       |
| 60     | barrel      | -       | 9          |
| 208    | barrel      | -       | 4          |
| 1000   | pallet tank | -       | 1          |

\*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.