



ARIAL G-LiFe SAE 75W-80 MTF



A multi-vehicle manual transmission fluid "MTF", based on high-quality synthetic base oils in combination with optimized additives

SKU: 301010

Categories: [Течности за ръчни скоростни кутии](#)

PRODUCT DESCRIPTION

A multi-vehicle manual transmission fluid "MTF", based on high-quality synthetic base oils in combination with optimized additives, resulting in the following properties:

- proven performance in European and Asian synchronizers
- superior bearing and gear protection
- excellent cleanliness
- good low temperature performance
- robust corrosion protection
- a long durability.

Application:

This multi-vehicle manual transmission oil has been specially developed for European and Asian vehicles (passenger cars and delivery vans), where the specified specifications are requested. This oil is also suitable for applications where the specified specifications are prescribed in combination with slightly different viscosities, such as 70W75, 70W90, 75W, 75W85 75W90 etc.

Performance Level:

API GL-4

BMW MTF LT-2 / LT3 / LT-4

FIAT MZ1 / MZ60768

Ford WSD-M2C200-C / WSS-M2C200-D2

GM 1940004 / 19259104 (BOT 303)

GM 1940182 / 1940764 / 1940768

Honda MTF / MTF-II / MTF-III
MB 235.10
NISSAN MT-XZ / MT-XZ TL (JR Type)
PSA B71 2330
Special gear oil, MTF 94
Tranself NFJ / NFP / TRJ / TRT / TRZ
Volvo 97308 / 97309
VW G 009 317 / G 052 171 / G 052 178
VW G 052 512 / G 052 527 / G 052 726
VW G 060 726 / G 070 726 / G 50

Typicals:

Density at 15 °C, kg/l: 0,854
Viscosity 40 °C, mm²/s: 45,20
Viscosity 100 °C, mm²/s: 9,00
Viscosity Index: 185
Flash Point COC, °C: 208
Pour Point, °C: -45
Total Base Number, mgKOH/g: 8,7

Packaging:

litres	packing	per box	per pallet
1	canister	12	*600
5	canister	4	*120
20	canister	-	24
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.