

## ARIAL ATF 8G



This premium synthetic product is specially formulated for the lubrication of ZF 8HP transmissions. This oil contributes greatly to realizing fuel saving and can be used amongst others in the ZF 8HP transmissions 8HP45, 8HP55, 8HP70 and 8HP90. It can also be used in certain ZF 6HP transmissions, which are used in various VAG models.

---

**Artikelnummer:** 302050

**Kategorien:** [Automatik-Getriebeöle](#)

A very high graded automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- important contribution fuel economy
- excellent lubrication
- very good resistance against oxidation and a very high thermal stability
- excellent and very stable friction characteristics that enable longer oil-replacement intervals
- excellent resistance against foaming
- excellent protection against wear
- a very high and stable viscosity index
- green coloured

### **Application:**

This premium synthetic product is specially formulated for the lubrication of ZF 8HP transmissions. This oil contributes greatly to realizing fuel saving and can be used amongst others in the ZF 8HP transmissions 8HP45, 8HP55, 8HP70 and 8HP90. It can also be used in certain ZF 6HP transmissions, which are used in various VAG models.

### **Performance Level:**

BMW 8322 2152426/2289720(ATF3+)

Chrysler 68157995AA

Fiat 9.55550-AV5  
Jaguar 02JDE 26444  
Land Rover LR023288  
VAG G-060-162

**Typicals:**

Density at 15 °C, kg/l: 0,842  
Viscosity 40 °C, mm<sup>2</sup>/s: 25,80  
Viscosity 100 °C, mm<sup>2</sup>/s: 6,00  
Viscosity Index: 190  
Flash Point COC, °C: 198  
Pour Point, °C: -51

**Packaging:**

litres	packing	per box	per pallet
1	canister	12	*600
5	canister	4	*120
20	canister	-	24
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1

\*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.