



ARIAL BRAKE FLUID DOT 4



Applicable for all hydraulic brake systems with drum or disk brakes requiring a synthetic brake fluid and where a brake fluid of the type DOT 4 is prescribed.

Artikelnummer: 701010

Kategorien: [Bremsflüssigkeiten](#)

A synthetic brake fluid having the following properties:

- good resistance against ageing
- a very good compatibility with seals and gaskets
- minimal corrosion tendency
- high wet boiling point
- optimal viscosity at low temperatures

Application:

Applicable for all hydraulic brake systems with drum or disk brakes requiring a synthetic brake fluid and where a brake fluid of the type DOT 4 is prescribed.

Performance Level:

FMVSS 116 DOT 4

SAE J1703, ISO 4925

Typicals:

Density at 15 °C, kg/l: 1,030

Viscosity -40 °C, mm²/s: 1200

Viscosity 100 °C, mm²/s: 2,30

Boiling Point (reflux) , °C: 263

Wet Boiling Point, °C: 168

pH - 50% in ethanol solution: 8,0

Packaging:

litres	packing	per box	per pallet
0,5	canister	4	*120
60	barrel	-	9
208	barrel	-	4

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.