

**ARIAL COOLANT D****лв. 1,900.00 с ДДС**

This coolant may be used all the year round in the cooling systems of gasoline and diesel engines. This coolant is ready for use and protects against freezing down to -38 °C.

Artikelnummer: 801010**Kategorien:** [Kühlmittel](#)

A "long life" OAT (Organic Additives Technology) automotive coolant based on monoethyleneglycol and demineralized water with addition of additives to obtain the following properties:

- a perfect protection of all types of metals that are used in engines and cooling systems
- a neutral behavior towards seals, gaskets and hoses
- a very good resistance against formation of foam
- nitrite, amine, phosphate and silicate free
- colored pink

Application:

This coolant may be used all the year round in the cooling systems of gasoline and diesel engines. This coolant is ready for use and protects against freezing down to -38 °C.

Performance Level:

ASTM D3306/D4985/D6210

Chrysler MS 9176

Cummins 85T8-2

DAF 74002

Detroit Diesel

Ford WSS-M97B44-D

GM 6277M

John Deere H 24 B1 & C1
Mack 014GS 17004
MAN 324 Typ SNF
MB 326.3
Leyland Trucks LTS 22 AF 10
Renault 41-01-001/--S Type D
Scania TB 1451
Volkswagen VW TL 774-F (G12 Plus)
Volvo VCS

Typicals:

Density at 15 °C, kg/l: 1,045

Crystallization Point, °C: -38

Packaging:

litres	packing	per box	per pallet
1	canister	12	*600
5	canister	4	*120
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.