

ARIAL COOLANT D

лв. 1,900.00 с ДДС

This coolant may be used all the year round in the cooling systems of gasoline and diesel engines. This coolant is ready for use and protects against freezing down to -38 °C.

Artikelnummer: 801010
Kategorien: Kühlmittel

A "long life" OAT (Organic Additives Technology) automotive coolant based on monoethyleneglycol and demineralized water with addition of additives to obtain the following properties:
- a perfect protection of all types of metals that are used in engines and cooling systems
- a neutral behavior towards seals, gaskets and hoses
- a very good resistance against formation of foam
- nitrite, amine, phosphate and silicate free
- colored pink

Application:
This coolant may be used all the year round in the cooling systems of gasoline and diesel engines. This coolant is ready for use and protects against freezing down to -38 °C.

Performance Level:
ASTM D3306/D4985/D6210
Chrysler MS 9176
Cummins 85T8-2
DAF 74002
Detroit Diesel
Ford WSS-M97B44-D
GM 6277M

John Deere H 24 B1 & C1
Mack 014GS 17004
MAN 324 Typ SNF
MB 326.3
Leyland Trucks LTS 22 AF 10
Renault 41-01-001/--S Type D
Scania TB 1451
Volkswagen VW TL 774-F (G12 Plus)
Volvo VCS

Typicals:
Density at 15 °C, kg/l: 1,045
Crystallization Point, °C: -38

Packaging:

litres	packing	per box	per pallet
1	canister	12	*600
5	canister	4	*120
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.