



ARIAL EXTLIFE SAE 10W-40 HC-L



A universal motor oil, recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans

SKU: 101014

Kategorie: [Motorenöle für den gemischten Fuhrpark](#), [PKW-Motorenöle](#)

PRODUKTBESCHREIBUNG

This universal motor oil is produced with special base oils that have a natural high viscosity index, to which additives are added to obtain the following properties:

- a high and stable viscosity index
- a fast cold start
- a strong resistance against oxidation
- a safe lubrication film at high temperature
- a good detergency and dispersion
- a strong protection against wear, corrosion and foaming

Application:

A universal motor oil, recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

Performance Level:

ACEA A3/B3, A3/B4-08

API SL/CF

MB 229.1

VW 501.01/505.00

Typicals:

Density at 15 °C, kg/l: 0,870

Viscosity -25 °C, mPa.s: 6000

Viscosity 40 °C, mm²/s: 92,00
Viscosity 100 °C, mm²/s: 13,80
Viscosity Index: 153
Flash Point COC, °C: 232
Pour Point, °C: -39
Total Base Number, mgKOH/g: 8,3
Sulphate Ash, %: 1,08

Packaging:

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
20		canister	-	24
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.