



ARIAL EXTLIFE SAE 5W-30 LL



High-performance engine oil developed specifically by BMW, Mercedes-Benz, Opel and VW for the requirements of the European market for models with exhaust after-treatment and turbocharging

SKU: 10107

Kategorie: [Motorenöle für den gemischten Fuhrpark](#), [PKW-Motorenöle](#)

PRODUKTBESCHREIBUNG

ARIAL ExTLiFe SAE 5W-30 LL is a specially developed engine oil based on selected HC synthetic base oils for modern passenger car [Otto](#) and diesel engines with exhaust after-treatment ([DPF = Diesel Particulate Filter](#)) and turbocharging

Application:

ARIAL ExTLiFe SAE 5W-30 LL has been developed specifically to meet the needs of modern petrol and diesel vehicles. It meets the requirements of many vehicle manufacturers and the ACEA C3 concerning a so-called low ash product. It is used in vehicles equipped with Otto and diesel engines, with or without exhaust after-treatment systems ([DPF = Diesel Particulate Filter](#)), according to the manufacturer's specification. It is therefore equally suitable for vehicles with or without turbocharging. In BMW vehicles, it is backward compatible with former specifications such as BMW LongLife-01/98. It covers the former specification GM-LL-A-025 or GM-LL-B-025 in Opel/GM vehicles

Benefits:

- First-class economy grade for multi-functional use in diesel and Otto engines from different manufacturers;
- The low sulphated ash, low phosphorus and sulphur content protects diesel particulate filters and catalytic converters;
- Hinders the formation of deposits in the engine. As a result, it guarantees first-rate operational safety performance and low maintenance costs;
- Low oil consumption due to a very low evaporation loss;

- Good cold-starting properties and rapid engine lubrication;
- Miscible and compatible with conventional and synthetic engine oils;

However, in order to exploit the full product benefits of ARIAL ExTLiFe SAE 5W-30 LL, a complete oil change is recommended

Performance Level:

ACEA C3

API SN, API SN Plus

BMW Longlife-04

GM dexos 2

MB 229.31/229.51/229.52

Opel OV040154701

VW 505.00/505.01

Typicals:

Density at 15 °C, kg/l: 0,848

Viscosity -30 °C, mPa.s: 5680

Viscosity 40 °C, mm²/s: 70,70Viscosity 100 °C, mm²/s: 12,30

Viscosity Index: 173

Flash Point COC, °C: 234

Pour Point, °C: -36

Total Base Number, mgKOH/g: 7,3

Sulphate Ash, %: 0,75

Packaging:

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
20		canister	-	24
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.