



## ARIAL TWO STROKE HS



This two-stroke engine oil is advised for the lubrication of high-speed air cooled two stroke engines under heavy duty load. This self-mixing two stroke engine oil may also be used for water cooled two stroke engines (radiator type cooling systems).

---

**Artikelnummer:** 501010

**Kategorien:** [2-Takt-Motorenöle](#)

## BESCHREIBUNG

A two stroke engine oil formulated with carefully selected high quality mineral and synthetic base oils and special two stroke additives to achieve the following properties:

- a perfect lubrication of all motor parts
- an active detergency, preventing from deposits in the combustion zone and at the scavenger ports
- preventing spark plugs from fouling, in this way securing an optimal output of the engine
- a very effective activity against wear and corrosion
- a very limited formation of smoke
- self mixing

### Application:

This two-stroke engine oil is advised for the lubrication of high-speed air cooled two stroke engines under heavy duty load. This self-mixing two stroke engine oil may also be used for water cooled two stroke engines (radiator type cooling systems).

### Performance Level:

API TC  
JASO FD  
Global GD  
Husqvarna 272

ISO-L-EGD  
2-Stroke DFI

**Typicals:**

Density at 15 °C, kg/l: 0,871  
Viscosity 40 °C, mm<sup>2</sup>/s: 64,60  
Viscosity 100 °C, mm<sup>2</sup>/s: 9,50  
Viscosity Index: 129  
Flash Point COC, °C: 116  
Pour Point, °C: -24  
Total Base Number, mgKOH/g: 1,4  
Sulphate Ash, %: 0,14

**Packaging:**

| litres | packing     | per box | per pallet |
|--------|-------------|---------|------------|
| 1      | canister    | 12      | *600       |
| 5      | canister    | 4       | *120       |
| 60     | barrel      | -       | 9          |
| 208    | barrel      | -       | 4          |
| 1000   | pallet tank | -       | 1          |

\*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.