



ARIAL UTTO HYDRAULIC



This universal tractor transmission oil (UTTO) has been developed for the hydraulics and transmissions of most generally used agricultural and road-construction equipment.

Artikelnummer: 201040

Kategorien: Multifunktionsöle (UTTO)

A nowadays universal hydraulic and transmission oil formulated with solvent refined base oils and selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- good extreme pressure- and anti-wear properties
- optimal friction properties and therefore applicable in systems with "wet" brakes
- excellent corrosion and foam preventing properties

Application:

This universal tractor transmission oil (UTTO) has been developed for the hydraulics and transmissions of most generally used agricultural and road-construction equipment.

Performance Level:

API GL-4
Allison C4
Case MS1206/MS1207/MS1209
Cat TO-2
CNH MAT 3525
Ford M2C134-D



John Deere J20C Massey Ferguson M1141/M1143 Volvo WB 101 ZF TE-ML 03E/05F/06K

Typicals:

Density at 15 °C, kg/l: 0,885 Viscosity 40 °C, mm²/s: 52,00 Viscosity 100 °C, mm²/s: 9,15

Viscosity Index: 156 Flash Point COC, °C: 244

Pour Point, °C: -39

Total Base Number, mgKOH/g: 7,3

Sulphate Ash, %: 1,19

Packaging:

litres	packing	per box	per pallet
20	canister	-	24
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1
*CP pallet size 114 x 114 cm.			