



ARIAL UTTO SYNTHETIC NF



This special synthetic UTTO has been developed for the hydraulics and transmissions of most generally used agricultural and road-construction equipment.

Artikelnummer: 201020

Kategorien: [Multifunktionsöle \(UTTO\)](#)

A modern synthetic UTTO formulated with a balanced mix of synthetic components and additives to obtain the following properties:

- a high and stable viscosity index
- a low pour point
- a very good stability against oxidation
- good extreme pressure- and anti-wear properties
- optimal friction properties and therefor applicable in systems with "wet" brakes
- excellent corrosion and foam preventing properties
- prevention of the so-called "stick-slip"

Application:

This special synthetic UTTO has been developed for the hydraulics and transmissions of most generally used agricultural and road-construction equipment.

Performance Level:

API GL-4

Allison C4

Case MS1207/MS1209

Cat TO-2

John Deere J20A

Massey Ferguson M1141/M1143/M1145
Volvo WB 102
ZF TE-ML 03E/05F

Typicals:

Density at 15 °C, kg/l: 0,852
Viscosity 40 °C, mm²/s: 38,00
Viscosity 100 °C, mm²/s: 7,63
Viscosity Index: 175
Flash Point COC, °C: 232
Pour Point, °C: -42

Packaging:

litres		packing		per box	per pallet
20	canister	-		24	
60	barrel	-		9	
208	barrel	-		4	
1000	pallet tank	-		1	

*CP pallet size 114 x 114 cm.