



ARIAL UTTO WB HT



This very high-quality universal tractor transmission oil (UTTO) has been developed for the heavy loaded hydraulics and transmissions, with or without wet brakes, of most generally used agricultural and road-construction equipment.

Artikelnummer: 201050

Kategorien: [Multifunktionsöle \(UTTO\)](#)

A very high quality universal hydraulic and transmission oil formulated with unconventional base oils and selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- a high thermal stability
- good extreme pressure- and anti-wear properties
- optimal friction properties and therefor applicable in systems with "wet" brakes
- excellent corrosion and foam preventing properties

Application:

This very high-quality universal tractor transmission oil (UTTO) has been developed for the heavy loaded hydraulics and transmissions, with or without wet brakes, of most generally used agricultural and road-construction equipment.

Performance Level:

API GL-4

Allison C4

Case MS1207/MS1209

Cat TO-2

John Deere J20A
Massey Ferguson M1141/M1143/M1145
Volvo WB 102
ZF TE-ML 03E/05F/06K

Typicals:

Density at 15 °C, kg/l: 0,856
Viscosity 40 °C, mm²/s: 39,30
Viscosity 100 °C, mm²/s: 7,70
Viscosity Index: 170
Flash Point COC, °C: 224
Pour Point, °C: -42

Packaging:

litres	packing		per box	per pallet
20	canister	-		24
60	barrel	-		9
208	barrel	-		4
1000	pallet tank	-		1

*CP pallet size 114 x 114 cm.