

ARIAL ATF 289

This fluid may be used for automatic gearboxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID fluid is required.

SKU: 302010
Categories: Automatic transmission fluids

A very high graded automatic transmission fluid formulated with solvent refined base oils and a number of selected additives to obtain the following properties:
- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured

Application:
This fluid may be used for automatic gearboxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID fluid is required.

Performance Level:
Allison C4
Cat TO-2
Ford Mercon/M2C138-CJ/166-H
GM Dexron IID
MAN 339 Typ Z1/V1
MB 236.6/236.7
Voith 55.6335 (G607)

ZF TE-ML 09/11A/14A

Typicals:
Density at 15 °C, kg/l: 0,857
Viscosity 40 °C, mm²/s: 43,20
Viscosity 100 °C, mm²/s: 8,25
Viscosity Index: 168
Flash Point COC, °C: 198
Pour Point, °C: -45
Total Base Number, mgKOH/g: 1,5
Sulphate Ash, %: 0,18

Packaging:

litres	packing	per box	per pallet
1	canister	12	*600
5	canister	4	*120
20	canister	-	24
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.