

ARIAL EXTLIFE SAE 0W-20

A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars, which prescribe an oil with the specification GM dexos1 ™ Gen 2.

SKU: 10101
Categories: Engine oils for passenger cars

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:
- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application:
A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars, which prescribe an oil with the specification GM dexos1 ™ Gen 2.

Performance Level:
API SP Resource Conserving
ILSAC GF-6A
GM dexos1 (TM) Gen 2
Chrysler MS 6395

Typicals:
Density at 15 °C, kg/l: 0,843

Viscosity -35 °C, mPa.s: 4940
Viscosity 40 °C, mm²/s: 44,00
Viscosity 100 °C, mm²/s: 8,60
Viscosity Index: 178
Flash Point COC, °C: 222
Pour Point, °C : -36
Total Base Number, mgKOH/g: 8,5
SulphateAsh, %: 0,89

Packaging:

litres	packing	per box	per pallet
1	canister	12	*600
5	canister	4	*120
20	canister	-	24
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.