



# ARIAL EXTLIFE SAE OW-40 RS



A universal, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbocharging, in passenger cars and delivery vans for which the most modern specifications are required.

SKU: 10105 Categories: Engine oils for passenger cars

A modern, synthetic, universal motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

# **Application:**

A universal, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

## **Performance Level:**

ACEA A3/B4 API SN/CF BMW Longlife-01 MB 229.3/226.5 Porsche A40 Renault RN0700/RN0710



#### VW 502.00/505.00

# **Typicals:**

Density at 15 °C, kg/l: 0,844 Viscosity -35 °C, mPa.s: 5620 Viscosity 40 °C, mm<sup>2</sup>/s: 75,90 Viscosity 100 °C, mm<sup>2</sup>/s: 13,50 Viscosity Index: 183 Flash Point COC, °C: 238 Pour Point, °C: -48 Total Base Number, mgKOH/g: 10,3 Sulphate Ash, %: 1,33

## **Packaging:**

litres	packing	per box	per pallet
1	canister	12	*600
5	canister	4	*120
20	canister	-	24
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1

\*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.