



## ARIAL EXTLIFE SAE 5W-30 GM



A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars, which prescribe an oil with the specification GM dexos1™ Gen 2

**SKU:** 101010

**Categories:** [Engine oils for passenger cars](#)

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

### Application:

A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars, which prescribe an oil with the specification GM dexos1™ Gen 2.

### Performance Level:

API SP Resource Conserving  
ILSAC GF-6A  
GM dexos1 (TM) Gen 2  
Chrysler MS 6395  
Ford M2C946-A

### Typicals:

Density at 15 °C, kg/l: 0,847  
Viscosity -30 °C, mPa.s: 4140  
Viscosity 40 °C, mm²/s: 61,80  
Viscosity 100 °C, mm²/s: 11,30  
Viscosity Index: 179  
Flash Point COC, °C: 224  
Pour Point, °C: -33  
Total Base Number, mgKOH/g: 8,5  
Sulphate Ash, %: 0,89

**Packaging:**

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
20		canister	-	24
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

\*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.