



## ARIAL RACING SAE 0W-30



A fully synthetic engine oil, designed for cars for race conditions where the highest performance is required. This oil has proven its quality under the most extreme conditions particularly in races.

---

**SKU:** 104010

**Categories:** [Engine oil for racing cars](#)

## PRODUCT DESCRIPTION

A fully synthetic engine oil based on carefully selected high quality synthetic base oils, among others ester, all of which already have a natural, high viscosity index and which advanced and well balanced additives in order to obtain the following properties:

- a very low tendency to evaporation
- a high and very stable viscosity index
- a good resistance against shearing
- a high resistance against aging
- a safe lubrication film at low and very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

### Application:

A fully synthetic engine oil, designed for cars for race conditions where the highest performance is required. This oil has proven its quality under the most extreme conditions particularly in races.

### Performance Level:

ACEA A3/B4

API SH/CF

API SN/CF\*

\* API SN quality only;

not-licensable due to phosphorus-limit.

**Typicals:**

Density at 15 °C, kg/l: 0,869

Viscosity -35 °C, mPa.s: 5710

Viscosity 40 °C, mm<sup>2</sup>/s: 50,30Viscosity 100 °C, mm<sup>2</sup>/s: 10,00

Viscosity Index: 190

Flash Point COC, °C: 246

Pour Point, °C: -51

Total Base Number, mgKOH/g: 10,3

Sulphate Ash, %: 1,33

**Packaging:**

	<b>litres</b>	<b>packing</b>	<b>per box</b>	<b>per pallet</b>
1		canister	12	*600
5		canister	4	*120
20		canister	-	24
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

\*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.