



## ARIAL UNILIFE SAE 5W-30 HC

лв. 1,902.02 с ДДС



This low SAPS oil is very suitable for use in on-road Euro 6 and off-road EU Stage IV engines in combination with diesel fuels with a low sulfur content, where the specified specifications are required. Suitable for the toughest operating conditions in engines with or without particulate filters and exhaust gas after treatment systems.

**SKU:** 103010

**Categories:** [Engine oils for commercial vehicles](#)

## VARIATIONS

Image	SKU	Price	Stock Status	Stock Quantity	Description	Liters
	AR003053070	лв. 1,902.02 с ДДС				208L

## PRODUCT DESCRIPTION

A top quality fuel-saving motor oil based on the latest additive technology in combination with specially selected synthetic base oils. This motor oil:

- prevents deposits in the engine
- prevents the formation of sediment and sludge
- extends the life of the particle filter
- has very strong anti-corrosion and anti-foaming properties
- prevents wear on piston rings and cylinder wall
- reduces fuel consumption
- contributes to a reduction in maintenance costs.

**Application:**

This low SAPS oil is very suitable for use in on-road Euro 6 and off-road EU Stage IV engines in combination with diesel fuels with a low sulfur content, where the specified specifications are required. Suitable for the toughest operating conditions in engines with or without particulate filters and exhaust gas after treatment systems. Can also be used in Volvo 13L Euro 6 Step D engines for which an oil with VDS-5 specification is prescribed.



[View product safety sheet](#)

**Performance Level:**

ACEA E6, E7, E9  
API CK-4/SN  
Deutz DQC IV-18 LA  
Mack EOS-4.5  
MB- 228.51  
Renault VI RLD-3  
Volvo VDS-4.5  
Cat ECF-3  
Cummins CES 20086  
Detroit Diesel DFS 93K222  
Ford WSS-M2C213-A  
JASO DH-2  
MAN M 3775  
MB 228.31 / 228.52  
MTU Type 3.1  
Scania Low Ash  
DAF Extended Drain, Iveco 18-1804 TLS E9

**Typicals:**

Density at 15 °C, kg/l: 0,856  
Viscosity -30 °C, mPa.s: 5860  
Viscosity 40 °C, mm<sup>2</sup>/s: 71,80  
Viscosity 100 °C, mm<sup>2</sup>/s: 12,10  
Viscosity Index: 162  
Flash Point COC, °C: 216  
Pour Point, °C: -42

Total Base Number, mgKOH/g: 9,8  
Sulphate Ash, %: 0,89

**Packaging:**

litres	packing		per box	per pallet
20	canister	-		24
208	barrel	-		4
1000	pallet tank	-		1

\*CP pallet size 114 x 114 cm.