



## ARIAL UTTO HYDRAULIC 540



This very high quality universal tractor transmission oil (UTTO) has been developed for heavy loaded hydraulics and transmissions, with or without wet brakes, of agricultural and road-construction equipment. This oil can also be used in certain continuously variable transmissions (CVT) of agricultural and road-construction equipment.

---

**SKU:** N/A

**Categories:** [Multifunctional oils \(UTTO\)](#)

A very high quality universal hydraulic and transmission oil formulated with high quality base oils and selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- a high thermal stability
- good extreme pressure- and anti-wear properties
- optimal friction properties and therefor applicable in systems with "wet" brakes
- excellent corrosion and foam preventing properties

### **Application:**

This very high quality universal tractor transmission oil (UTTO) has been developed for heavy loaded hydraulics and transmissions, with or without wet brakes, of agricultural and road-construction equipment. This oil can also be used in certain continuously variable transmissions (CVT) of agricultural and road-construction equipment.

### **Performance Level:**

API GL-4

Allison C4

Cat TO-2  
Case MS 1210  
CNH MAT 3540/3525  
FNHA-2-C-200.00/201.00  
Ford M2C86-C/M2C134-D  
John Deere J20C/D  
Massey Ferguson M1141/M1143/M1145  
Valtra G2-08  
Volvo WB 101  
ZF TE-ML 03E/05F/06K/17E/21F

**Typicals:**

Density at 15 °C, kg/l: 0,867  
Viscosity 40 °C, mm<sup>2</sup>/s: 60,00  
Viscosity 100 °C, mm<sup>2</sup>/s: 9,30  
Viscosity Index: 136  
Flash Point COC, °C: 215  
Pour Point, °C: -45  
Total Base Number, mgKOH/g: 9,9  
Sulphate Ash, %: 1,49

**Packaging:**

litres	packing		per box	per pallet
20	canister	-		24
60	barrel	-		9
208	barrel	-		4
1000	pallet tank	-		1

\*CP pallet size 114 x 114 cm.