



ARIAL ATF 7G



This fluid may be used for automatic transmissions of different car manufacturers.

SKU: 302040

Categories: [Трансмиссионные масла для АКПП](#)

PRODUCT DESCRIPTION

A very high graded automatic transmission fluid formulated with a number of special selected base oils and additives to obtain the following properties:

- a high shifting comfort
- a very low pour point
- very good stability against oxidation
- very good thermal properties
- a positive activity against wear, corrosion and foam
- a constant friction stability over lifetime ensuring perfect clutch operation
- a perfect compatibility with seals and non-ferro metals
- extremely resistant against shudder vibration
- as a result of the perfect viscosity grade a fuel-efficiency potential
- red coloured

Application:

This fluid may be used for automatic transmissions of different car manufacturers.

Performance Level:

Allison C4/TES-389
Chrysler ATF+/+2/+3/+4
Ford Mercon V/Mercon/WSS-M2C922-A1
GM Dexron II/IID/IIE/IIIG/IIIH
Honda ATF-Z1 (except in CVT)

Hyundai/Kia SP-II/SP-III
Isuzu ATF II/III
Jaguar JLM 20238/20292/21044
JASO M315 Type 1A
Mazda M-III/Type T-IV
MB 236.3/236.5/236.6/236.7/236.8
MB 236.9/236.10/236.11/236.91
Mitsubishi SP-II/SP-III/ATF J-2
Nissan Matic D/J/K/W
Subaru ATF HP, Suzuki ATF 3314/3317
Toyota Type DII/T/T-III/T-IV
VAG G-052-025/052-055/052-162/052-990/055-025
Volvo 1161540, ZF TE-ML 11A/11B

Typicals:

Density at 15 °C, kg/l: 0,855
Viscosity -30 °C, mPa.s: 2980
Viscosity 40 °C, mm²/s: 33,10
Viscosity 100 °C, mm²/s: 7,10
Viscosity Index: 185
Flash Point COC, °C: 200
Pour Point, °C: -54

Packaging:

litres	packing	per box	per pallet
1	canister	12	*600
5	canister	4	*120
20	canister	-	24
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.