

ARIAL ATF 9G



This premium synthetic product is specially formulated for the lubrication of certain Mercedes-Benz automatic transmissions with 9 gears. This oil contributes significantly to realizing fuel saving and can be used in automatic transmissions where an oil with the specification MB 236.17 is prescribed.

SKU: 302060

Categories: [Трансмиссионные масла для АКПП](#)

A very high graded, extremely low-viscosity automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- excellent contribution to fuel economy
- excellent lubrication
- very good resistance against oxidation
- very good thermal stability
- excellent and very stable friction characteristics
- excellent resistance against corrosion and foaming
- excellent protection against wear
- a very high and stable viscosity index

Application:

This premium synthetic product is specially formulated for the lubrication of certain Mercedes-Benz automatic transmissions with 9 gears. This oil contributes significantly to realizing fuel saving and can be used in automatic transmissions where an oil with the specification MB 236.17 is prescribed.

Performance Level:

MB 236.17

Typicals:

Density at 15 °C, kg/l: 0,835
Viscosity 40 °C, mm²/s: 17,10
Viscosity 100 °C, mm²/s: 4,23
Viscosity Index: 161
Flash Point COC, °C: 174
Pour Point, °C: -57

Packaging:

litres	packing	per box	per pallet
1	canister	12	*600
5	canister	4	*120
20	canister	-	24
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.