



ARIAL ATF DMM



This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID, IIE, IIIF, IIIG or IIH fluid is required.

SKU: 302020

Categories: [Трансмиссионные масла для АКПП](#)

PRODUCT DESCRIPTION

A very high graded automatic transmission fluid formulated with solvent refined and synthetic base oils and a number of selected additives to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- very good stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured

Application:

This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID, IIE, IIIF, IIIG or IIH fluid is required.

Performance Level:

Allison C4/TES-389
Cat TO-2
Ford Mercon/M2C138-CJ/166-H
GM Dexron IID/IIE/IIIF/IIIG/IIH
MAN 339 Typ Z1/V1
MB 236.1/236.5/236.6/236.7/236.9

Voith 55.6335 (G607)

Volvo 97341

ZF TE-ML 02F/03D/04D/09A/09B/11A/11B/14A/17C

Typicals:

Density at 15 °C, kg/l: 0,851

Viscosity 40 °C, mm²/s: 37,70

Viscosity 100 °C, mm²/s: 7,60

Viscosity Index: 175

Flash Point COC, °C: 210

Pour Point, °C: -51

Packaging:

litres	packing	per box	per pallet
1	canister	12	*600
5	canister	4	*120
20	canister	-	24
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.