

**ARIAL COOLANT D****лв. 1,900.00 с ДДС**

This coolant may be used all the year round in the cooling systems of gasoline and diesel engines. This coolant is ready for use and protects against freezing down to -38 °C.

---

**SKU:** 801010**Categories:** [Антифриз](#)**PRODUCT DESCRIPTION**

A "long life" OAT (Organic Additives Technology) automotive coolant based on monoethyleneglycol and demineralized water with addition of additives to obtain the following properties:

- a perfect protection of all types of metals that are used in engines and cooling systems
- a neutral behavior towards seals, gaskets and hoses
- a very good resistance against formation of foam
- nitrite, amine, phosphate and silicate free
- colored pink

**Application:**

This coolant may be used all the year round in the cooling systems of gasoline and diesel engines. This coolant is ready for use and protects against freezing down to -38 °C.

**Performance Level:**

ASTM D3306/D4985/D6210

Chrysler MS 9176

Cummins 85T8-2

DAF 74002

Detroit Diesel

Ford WSS-M97B44-D

GM 6277M  
John Deere H 24 B1 & C1  
Mack 014GS 17004  
MAN 324 Typ SNF  
MB 326.3  
Leyland Trucks LTS 22 AF 10  
Renault 41-01-001/--S Type D  
Scania TB 1451  
Volkswagen VW TL 774-F (G12 Plus)  
Volvo VCS

**Typicals:**

Density at 15 °C, kg/l: 1,045

Crystallization Point, °C: -38

**Packaging:**

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

\*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.