



ARIAL EXTLIFE SAE 5W-30 LL

лв. 14.38 - лв. 500.08 с ДДС



This universal, fuel saving synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application.

***Online sales are carried out only on the territory of Bulgaria**

SKU: 10107

Categories: [Моторные масла для смешанных автопарков](#), [Моторные масла для легковых автомобилей](#)

VARIATIONS




Image	SKU	Price	Stock Status	Stock Quantity	Description Liters
	AR001053020	лв. 14.38 с ДДС			1L

Image	SKU	Price	Stock Status	Stock Quantity	Description	Liters
	AR001053040	лв. 65.28 с ДДС				5L
	AR001053060	лв. 500.08 с ДДС				60L

PRODUCT DESCRIPTION

A universal, synthetic fuel economy motor oil developed according the most recent technology and based on specially selected synthetic base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application:

This universal, fuel saving synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application.

Performance Level:

ACEA C3

API SN, API SN Plus

MB- 229.31/229.51/229.52

BMW Longlife-04

GM dexos 2

Opel OV0401547

VW 505.00/505.01

Typicals:

Density at 15 °C, kg/l: 0,852

Viscosity -30 °C, mPa.s: 5880

Viscosity 40 °C, mm²/s: 68,60

Viscosity 100 °C, mm²/s: 12,30

Viscosity Index: 175

Flash Point COC, °C: 228

Pour Point, °C: -36

Total Base Number, mgKOH/g: 7,3

Sulphate Ash, %: 0,75

Packaging:

litres	packing	per box	per pallet
1	canister	12	*600
5	canister	4	*120
20	canister	-	24
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.