



ARIAL EXTLIFE SAE 5W-40 MFS



This universal synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover, this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit.

SKU: 101013

Categories: [Моторные масла для легковых автомобилей](#)

PRODUCT DESCRIPTION

This motor oil is based on high quality solvent refined mineral and synthetic base oils. By adding a well-balanced choice of additives, the following properties are obtained:

- a high and stable viscosity index
- a fast cold start
- a strong resistance against oxidation
- a good detergency and dispersion
- a safe lubrication film at high temperatures
- a strong protection against wear, corrosion and foaming

Application:

This universal synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover, this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application.

Performance Level:

ACEA C3
API SN, API SN Plus
BMW Longlife-04
MB 229.51/229.52
VW 505.00/505.01

Typicals:

Density at 15 °C, kg/l: 0,850

Viscosity -30 °C, mPa.s: 5530

Viscosity 40 °C, mm²/s: 78,80

Viscosity 100 °C, mm²/s: 13,60

Viscosity Index: 179

Flash Point COC, °C: 230

Pour Point, °C: -39

Total Base Number, mgKOH/g: 7,0

Sulphate Ash, %: 0,75

Packaging:

litres	packing	per box	per pallet
1	canister	12	*600
5	canister	4	*120
20	canister	-	24
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.