



## ARIAL FS 2T AIR COOLED



This two-stroke engine oil is specially suitable for the lubrication of high speed two stroke engines under heavy duty load. This self-mixing two stroke engine oil is also advised for use in two stroke scooters, on which often radiator coolers are fitted.

---

**SKU:** 501020

**Categories:** [2-тактные моторные масла](#)

## PRODUCT DESCRIPTION

A full-synthetic two stroke engine oil formulated with carefully selected high quality synthetic base oils (ester) and special two stroke additives to achieve the following properties:

- a perfect lubrication of all motor parts
- a very active detergency, preventing from deposits in the combustion zone and at the scavenger ports
- preventing spark plugs from fouling, in this way securing an optimal output of the engine
- a very strong activity against wear and corrosion
- a very limited formation of smoke
- self-mixing

### Application:

This two-stroke engine oil is specially suitable for the lubrication of high speed two stroke engines under heavy duty load. This self-mixing two stroke engine oil is also advised for use in two stroke scooters, on which often radiator coolers are fitted.

### Performance Level:

API TC  
JASO FD  
Husqvarna

ISO-L-EGD  
Piaggio Hexagon

**Typicals:**

Density at 15 °C, kg/l: 0,880  
Viscosity 40 °C, mm<sup>2</sup>/s: 70,50  
Viscosity 100 °C, mm<sup>2</sup>/s: 11,00  
Viscosity Index: 147  
Flash Point PM, °C: 78  
Pour Point, °C: -45  
Total Base Number, mgKOH/g: 2,9  
Sulphate Ash, %: 0,12

**Packaging:**

| litres | packing     | per box | per pallet |
|--------|-------------|---------|------------|
| 1      | canister    | 12      | *600       |
| 5      | canister    | 4       | *120       |
| 60     | barrel      | -       | 9          |
| 208    | barrel      | -       | 4          |
| 1000   | pallet tank | -       | 1          |

\*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.