

**ARIAL HVLP 32****лв. 1,293.00 с ДДС**

ARIAL HVLP 32 is a hydraulic oil containing additives to prevent corrosion, wear and friction. ARIAL HVLP 32 contains agents that ensure clean hydraulics.

SKU: AR001951370**Categories:** [Гидравлические масла](#)

ARIAL HVLP 32 is a hydraulic oil containing additives to prevent corrosion, wear and friction. ARIAL HVLP 32

contains agents that ensure clean hydraulics.

ARIAL HVLP 32 is a multi-purpose lubricating oil with a high load-bearing capacity that improves performance in mixed-friction conditions, thus counteracting friction or frictional vibrations due to stick-slip. A special focus should therefore be placed on its good wear protection and cleaning properties as well as its good sludge carrying capacity.

ARIAL HVLP 32 exceeds the requirements concerning hydraulic oils in compliance with DIN 51524 Part 2 for hydraulics.

[Information on hydraulic liquids »](#)

Performance Level:

AFNOR NF E 48-603 HV

ASTM D 6158 HV

Cincinnati Machine P-68

Denison HF-0/HF-1/HF-2

DIN 51524-3 HVLP

Eaton Brochure 694 for 35VQ25A

GM LS-2

ISO 11158 HV

Benefits:

High level of wear protection Good corrosion protection Thermally stable
Resistant to oxidation
Good air separation ability and foaming behaviour Hydrolytic resistance

Recommendation:

Machine tools, construction and textile machinery Run-in oil for units and machines
Oil for functional tests
Break-in oil, also for overseas exports
In the event of wet deliveries Electrical multi-plate clutches Foundries
Cement factories
Hydraulics used in agriculture

Typicals:

Density at 15 °C, kg/l: 0,857
Viscosity 40 °C, mm²/s: 32,00
Viscosity 100 °C, mm²/s: 6,44
Viscosity Index: 159
Flash Point COC, °C: 190
Pour Point, °C: -39
Acid number, mgKOH/g: 0,40
Sulphate Ash, %: 0,06

Packaging:

litres	packing		per box	per pallet
20	canister	-	24	
60	barrel	-	9	
208	barrel	-	4	
1000	pallet tank	-	1	

*CP pallet size 114 x 114 cm.