



ARIAL TRUCK RACING SAE 15W-60



A fully synthetic engine oil, designed for cars for race conditions where the highest performance is required. This oil has proven its quality under the most extreme conditions particularly in races.

SKU: 103060

Categories: [Моторные масла для гоночных автомобилей](#), [Моторные масла для грузового транспорта](#)

PRODUCT DESCRIPTION

A fully synthetic robust engine oil developed for use under extreme severe conditions. This product is specially designed for trucks that are used in "off-road races". Through the use of a special combination of synthetic base oils, among others ester and advanced additives has this product a very strong lubricant film. This engine oil has through its composition a high resistance to oxidation and viscosity loss under high load. This engine oil has the following typical properties:

- a very low tendency to evaporation
- a high and very stable viscosity index
- a good resistance against shearing
- a high resistance against aging
- a safe lubrication film at low and very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

Application:

A fully synthetic engine oil, designed for cars for race conditions where the highest performance is required. This oil has proven its quality under the most extreme conditions particularly in races.



Performance Level:

ACEA E6, E7, E9

API CJ-4

Typicals:

Density at 15 °C, kg/l: 0,862

Viscosity -20 °C, mPa.s: 6430

Viscosity 40 °C, mm²/s: 166,00

Viscosity 100 °C, mm²/s: 22,90

Viscosity Index: 166

Flash Point COC, °C: 228

Pour Point, °C: -54

Total Base Number, mgKOH/g: 9,6

Packaging:

litres	packing	per box	per pallet
20	canister	-	24
208	barrel	-	4
1000	pallet tank	-	1

litres	packing	per box	per pallet
--------	---------	---------	------------

*CP pallet size 114 x 114 cm.

