



## ARIAL TWO STROKE DFI



This ashless two stroke engine oil is excellent suitable for application in the higher horsepower, water-cooled two stroke outboard engines with Direct Fuel Injection.

---

**SKU:** 601020

**Categories:** [Масла для 2-тактных лодочных двигателей](#)

A two-stroke engine oil formulated with carefully selected high quality base oils and special ashless two stroke additives. This well-balanced composition gives this engine oil the following properties:

- an excellent lubricity
- a minimal carbon build-up
- a reduced spark plug fouling
- a limited formation of smoke
- a powerful detergency and activity against wear and corrosion
- excellent high temperature properties

### Application:

This ashless two stroke engine oil is excellent suitable for application in the higher horsepower, water-cooled two stroke outboard engines with Direct Fuel Injection.

### Performance Level:

NMMA TC-W3

### Typicals:

Density at 15 °C, kg/l: 0,871

Viscosity 40 °C, mm<sup>2</sup>/s: 43,50

Viscosity 100 °C, mm<sup>2</sup>/s: 7,33

Viscosity Index: 132

Flash Point COC, °C: 90

Pour Point, °C: -42

Total Base Number, mgKOH/g: 10,6

### Packaging:

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

\*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.