



## **ARIAL UNILIFE 10W-40 TRUCK**

лв. 1,410.31 с ддС



A top quality diesel engine oil based on the latest additive technology combined with special and synthetic base oils.

**SKU:** 103040

Categories: Моторные масла для грузового

транспорта

### **VARIATIONS**

lmage	SKU	Price	Stock Status	Stock Quantity	Description Liters
<u>₽</u>	AR003154070 дд	s. 1,410.31 c qC			208L

## PRODUCT DESCRIPTION

A top quality diesel engine oil based on the latest additive technology combined with special and synthetic base oils. This engine oil has the following properties:

- a very powerful detergency prevents deposits in the engine
- a very strong dispersion that prevents from precipitation and sludge
- a decreased tendency to particle forming increases the lifetime of the particle filter
- a powerful activity against corrosion and foam
- a high and stable natural viscosity index



- a low sulphated ash, phosphor and sulphur content (low SAPS)
- a powerful activity against wear, resulting in strongly reduced wear of piston-rings and cylinderliners
- contributes to a decrease of the maintenance costs

# **Application:**

This lubricant has mainly been developed for heavy diesel engines even under the toughest operation conditions and all the year round. This product is very suitable for Euro 4, Euro 5 and Euro 6 engines in combination with diesel fuel with a low Sulphur content. This engine oil is also suitable for application in engines with or without particle filters and exhaust catalysts. This motor oil is one of the groups "low SAPS" lubricants.

#### **Performance Level:**

ACEA E6, E7
API CI-4
Cummins CES 20076/20077
DAF Long Drain
Deutz DQC IV-10 LA
JASO DH-2
Mack EO-N
MAN M 3477/M 3271-1
MB 228.51
MTU Type 3.1

Renault VI RXD/RGD/RLD-2

## **Typicals:**

Volvo VDS-3

Density at 15 °C, kg/l: 0,863 Viscosity -25 °C, mPa.s: 5730 Viscosity 40 °C, mm²/s: 87,00 Viscosity 100 °C, mm²/s: 13,40

Viscosity Index: 155 Flash Point COC, °C: 222 Pour Point, °C: -36

Total Base Number, mgKOH/g: 10,0

Sulphate Ash, %: 0,95

## Packaging:

litres	packing	per box	per pallet
20	canister	-	24
208	barrel	-	4
1000	pallet tank	-	1



litres packing per box per pallet

\*CP pallet size 114 x 114 cm.