



## ARIAL UNILIFE SAE 10W-30 ULTRA

лв. 1,360.38 с ДДС



This engine lubricant is applicable to gasoline and diesel engines (normally- or turbo-aspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved.

**SKU:** 103020

**Categories:** [Моторные масла для грузового транспорта](#), [Моторные масла для смешанных автопарков](#)

## VARIATIONS

Image	SKU	Price	Stock Status	Stock Quantity	Description Liters
	AR002103070	лв. 1,360.38 с ДДС			208L

## PRODUCT DESCRIPTION

A gasoline- and diesel engine oil, formulated with solvent refined base oils and a well-balanced choice

of additives. This engine oil has the following properties:

- a very powerful detergency prevents deposits in the engine
- a very strong dispersion that prevents from precipitation and sludge
- a powerful activity against corrosion and foam
- a high and stable viscosity index
- a powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners

### **Application:**

This engine lubricant is applicable to gasoline and diesel engines (normally- or turbo-aspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This special quality of engine oil is mainly developed to allow extended oil drain intervals and to prevent "bore polishing" (=cylinder-wear) in diesel engines. This product is suitable for application in Euro 4 and Euro 5 engines.

### **Performance Level:**

ACEA E7  
API CI-4/SH  
Cat ECF-1-a/ECF-2  
Cummins CES 20077/20078  
Deutz DQC III-10  
MAN M 3275-1  
MB 228.3  
MTU Type 2  
Renault VI RLD-2

### **Typicals:**

Density at 15 °C, kg/l: 0,865  
Viscosity -25 °C, mPa.s: 6760  
Viscosity 40 °C, mm<sup>2</sup>/s: 75,10  
Viscosity 100 °C, mm<sup>2</sup>/s: 11,40  
Viscosity Index: 144  
Flash Point COC, °C: 216  
Pour Point, °C: -36  
Total Base Number, mgKOH/g: 11,1  
Sulphate Ash, %: 1,43

### **Packaging:**

litres		packing	per box	per pallet
20	canister	-	24	
208	barrel	-	4	

litres	packing	per box	per pallet
1000	pallet tank	-	1
*CP pallet size 114 x 114 cm.			