



ARIAL UNILIFE 15W-40 HD

лв. 1,254.57 с ДДС



This universal lubricating oil is suitable for gasoline or diesel engines, with or without super-charging. This motor oil is suitable for application in mixed fleets.

SKU: 103050

Categories: [Моторные масла для грузового транспорта](#), [Моторные масла для смешанных автопарков](#)

VARIATIONS

Image	SKU	Price	Stock Status	Stock Quantity	Description Liters
	AR001154070	лв. 1,254.57 с ДДС			208L

A gasoline- and diesel engine oil, formulated with solvent refined base oils and a well-balanced choice of additives. This engine oil has the following properties:

- a very powerful detergency prevents deposits in the engine
- a very strong dispersion that prevents from precipitation and sludge
- a powerful activity against corrosion and foam
- a high and stable viscosity index

- a powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners

Application:

This universal lubricating oil is suitable for gasoline or diesel engines, with or without super-charging. This motor oil is suitable for application in mixed fleets.

Performance Level:

ACEA E7
API CH-4/SJ
Cat ECF-1-a
Cummins CES 20076/20077
Deutz DQC III-10
MAN M 3275-1
MB 228.1
MTU Type 2
Volvo VDS-2

Typicals:

Density at 15 °C, kg/l: 0,884
Viscosity -20 °C, mPa.s: 5700
Viscosity 40 °C, mm²/s: 107,00
Viscosity 100 °C, mm²/s: 14,50
Viscosity Index: 140
Flash Point COC, °C: 220
Pour Point, °C: -33
Total Base Number, mgKOH/g: 11,1
Sulphate Ash, %: 1,43

Packaging:

litres		packing		per box	per pallet
20	canister	-		24	
208	barrel	-		4	
1000	pallet tank	-		1	

*CP pallet size 114 x 114 cm.